

ScrollSander Sanding Belts

NOW from
OLSON®



Sand
convex or
concave
edges

Reach into
intersections

Correct
wandering
from a
cutting
line

Remove
bumps,
burns, and
feathering

Packaged
to sell
with
Olson
Scroll
Saw
Blades

Recommendations:

Fits most 5" scroll saws (Craftsman®, Delta®, DeWalt®, Excalibur®, Ryobi®), but modifications may be required to throat insert or table opening depending upon width of sander used. Be sure to check your table/ throat plate opening before purchasing sanders. DeWalt® & Excalibur® Scroll Saws only accept the 1/4" sanders unless you drill the table hole larger.

Dremel® 1670, 1671 & 1680: use pin end sanders. Remove nub of plastic at gate to fit into clamp, if necessary.

Delta®: use side mount, cut table insert to fit sander, or remove table insert.

Ryobi® SC 160: use pin end sanders. Ryobi® SC 162, 162VS & 165: use plain end sanders only.

Hegner®: use pin end sanders.

Does not fit RBI®, Reliant®, or Moto-Shop®.

Plain end sanders fit most conversion kits for mounting blades with plain ends on pin end saws.

U.S. Patent No.: 6,129,617



1/4"
wide

4-pk
Part No. Grit

Pin End

SC91262BL Assorted: 180, 220 and (2) 120

SC91212BL 120

SC91218BL 180

SC91222BL 220

Plain End

SC92262BL Assorted: 180, 220 and (2) 120

SC92212BL 120

SC92218BL 180

SC92222BL 220

plain end
shown

1/2"
wide

4-pk
Part No. Grit

Pin End

SC91564BL Assorted
80, 120, 180, 220

SC91508BL 80

SC91512BL 120

SC91518BL 180

SC91522BL 220

Plain End

SC92564BL Assorted
80, 120, 180, 220

SC92508BL 80

SC92512BL 120

SC92518BL 180

SC92522BL 220